

Gravely Handle Grip Installation Instructions

Thank you for your purchase of our handlegrips - we appreciate your business!

We recommend that you install your new grips by following these simple instructions:

1. Remove the old grip. In most cases, the grip will not come off easily. A common removal method is to drive it off of the handlebar using a flat-bladed screwdriver and a hammer. It can also be cut off of the handlebar using a sharp utility knife, as long as it is done with care.
2. Scrape and sand the grip mounting area of the handlebar using a course grade of sand paper. You want the area clean, but slightly rough.

Note: If you have the optional handlebar-mounted kill switch in the end of the right handlebar, sand the end of that handle bar and the metal shell of the kill switch to ensure the switch has a good ground.

3. The grip is slightly smaller in diameter than the handle bar, so you must soften the vinyl by warming the open end of it in hot water or using a blow dryer. Don't warm the entire grip or it will be too flexible to drive it all the way down on the handle bar. If you feel the need to lubricate the end, use a dab of dish soap around the opening, but be careful, as too much soap will cause the grip to slide off.
4. Once the grip starts onto the handle bar, tap the closed end with a piece of board or a rubber mallet.
5. The small grips will require wrapping the lever with some duct tape or putting a piece of 5/16" ID thin wall plastic tubing (included) on it, due to the diameter of the grip being 3/32" larger than the lever. Heat the piece of tubing with hot water and then tap it on the lever shaft. It should be a snug fit and the grip will slide over it and fit nicely.

Again, we thank you for your purchase, and look forward to be of service to you again soon!

Galen Suiter
Suiter & Co.
P. O. Box 134
Coosada, Alabama 36020
Tele: (334) 285-3109
E-mail: gravely@elmore.rr.com

